



SECURITY PRODUCTS

X2-SIREN-100 DATASHEET

Overview

The X2-SIREN-100 is a self-contained high-security external siren with integrated strobe/sounder and rechargeable back up battery. It can be configured to suit most industry panels, and supports 5 selectable EOL resistor values for the tamper circuit and is enclosed in a UV resistant PC housing.

Pronto Part Number	Description
X2-SIREN-100	X2 Satellite Combo Siren & Strobe with NiMh Backup Battery

Features:

- Dual tamper protection from the outer cover removal or wall removal
- Equipped with internal rechargeable 7.2V Ni-Mh battery
- Selectable LED status indicators
- Six high intensity strobe LEDs
- Four selectable siren timers
- Power LED
- Battery LED
- Rear cable guides

Specifications:

Operating Voltage	13.5VDC
Current Consumption	20mA at 13.5VDC
Backup Battery	7.2V 500mA rechargeable
Siren Current	220mA at 12Vdc
Flash Current	300mA at 12Vdc
Siren Output	110db
Flash Rate	90 times per minute
Timers	1 min, 3 min, 15 min, continuous
Tamper	Selectable EOLs
Operating Temperature	-25°C to +70°C
Housing	PC with UV Resistant
Lens	Blue
Dimensions	210H x 138W x 50D mm



Additional Information:

Warranty	2 years
----------	---------

*Features and specifications are subject to change without notice. E&OE.